

3Ton Oil To Lithium Battery Forklift With Optional Lifting Height

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: goodsense
- Model Number: FB30LE
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Bare packaging
- Delivery Time: 30-40work days
- Payment Terms: T/T




Product Specification

- Rated Capacity: 3000kg
- Load Centre: 500mm
- Place Of Origin: China
- Brand Name: Goodsense
- Name: Forklift
- Condition: New
- Energy Supply: Reference Introduction
- Advantage: Small Vibration And Noise
- Highlight: 3Ton lithium battery forklift,
Oil to lithium battery forklift,
3Ton lithium ion battery forklift trucks



More Images



for more products please visit us on rdforklift.com

Product Description

GOODSENSE LE series 3-3.8t oil-to-electric forklift is a new energy oil-to-electric product developed on the platform of TCF series internal combustion forklift, applying the shape, chassis and gantry system of the internal combustion vehicle, and integrating the last lithium battery control technology.

Efficient Drive System

H-type compact structure drive unit, low center gravity, more reasonable layout, and more stable driving. New type of maintenance-free AC motor, high transmission efficiency, lower maintenance and field cost.

Flexible Steering System

Adopt dynamic load-sensing priority steering system to make steering response faster and driving more stable. Frame and steering axle are connected by suspension. Special rubber pads effectively buffer shock absorption.



Comfortable Operation Space

The ergonomic all-round operation space layout of 3 Ton Oil to Electric Lithium Battery Forklift is optimized to create a good, comfortable and convenient driving experience for the operator.

- Front hydraulic joystick
- Inclination adjustable small diameter steering wheel
- Sawtooth anti-skid pedals
- Wide field of view mast design



Characteristic		
Model		FB30LE
Power Type		Lithium Battery (Electric)
Rated Capacity	kg	3000
Load Centre	mm	500
Service weight	kg	4000
Tyre & Chassis		
Tyre Type(Front/Rear)		Pneumatic
Wheel number X = drive wheel (Front/Rear)		2X/2
Tyre Size(Front)		28x9-15-14PR
Tyre Size(Rear)		6.50-10-10PR
Front Tread	mm	1000
Rear Tread	mm	960
Wheelbase	mm	1800
Size		
Fork Size(LxWxT)	mm	1070x125x45
Mast Tilt Angle(F/R)	deg	6/12
Lift Height	mm	3000
Mast Lowered Height	mm	2115
Free Lift Height	mm	125
Mast Extended Height	mm	4175
Backrest Height	mm	1140
Fork Adjust Distance	mm	250-1100
Length to Face of Fork	mm	2781
Overall Width	mm	1230
Overhead Guard Height	mm	2150
Distance From Roof to Seat	mm	1010
Front Overhang	mm	481
Rear Overhang	mm	500

Turning Radius(outside)	mm	2540
Ground Clearance(Bottom of mast)	mm	140
Min.intersecting aisle	mm	2600
Min.right angle stacking aisle width	mm	4280



Taizhou Ruidong Import and Export Co., Ltd



18367688514



gjg_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China